



PRODUCT DATA SHEET

DuraMAX® CVT FLUIDS

SYNTHETIC CONTINUOUSLY VARIABLE TRANSMISSION FLUID



PRODUCT DESCRIPTION

DuraMAX® CVT FLUIDS specifically formulated for today's technologically-sophisticated continuously variable transmissions. They are formulated with premium synthetic base stocks, long-life friction modifiers, special anti-wear additives, and shear-stable viscosity modifiers to ensure maximum protection against wear, shuddering and slippage. DuraMAX CVT Fluids are recommended for use in most belt and chain-driven continuously variable transmissions found in modern North American, Asian and European automobiles.

FEATURES AND BENEFITS

DuraMAX CVT FLUIDS meet the performance requirements of most vehicles fitted with belt or chain continuously variable transmissions. Their full synthetic formulas provide excellent metal-on-metal friction protection to help prevent belt and torque converter slippage, even in severe operating conditions. They maintain excellent shear stability and guard against the harmful effects of viscosity loss, oxidation and the formation of sludge which can damage critical transmission components. DuraMAX CVT fluids perform exceptionally well in cold weather conditions where rapid fluid flow is vital for smooth transmission operation.

PRODUCT APPLICATIONS

Audi Multitronic
 BMW Mini Cooper EZL 799A/ 83 22 0 136 376/ 83 22 0 429 154
 Citroen PSA Standard 9735EF
 Daihatsu AMMIX CVTF DFE
 Daihatsu AMMIX CVT Fluid DC
 Daihatsu AMMIX CVT Fluid DFC
 Daihatsu Fluid TC
 Dodge/Jeep/Chrysler NS-2
 Dodge/Chrysler/Jeep/Mopar CVT+4
 Fiat Tutela Car CVT N.G
 Ford WSD-M2C-199A
 Fujijyuuko i-CVTF FG
 GM/Saturn DEX-CVT, GM 1940713 and 1940714
 GM/Saturn CVTF I-Green2
 GM VT40 /GM HP CVT
 Honda HMMF (for CVT without starting clutch)
 Honda HCF2
 Honda Z-1 (CVT without starting clutch)
 Honda CVT (not recommended for any Honda with starting clutch)
 Honda Ultra HEVF-Type 1
 Hyundai/Kia CVT-1, SP CVT-1 and CVT-J1
 Hyundai/Kia SP III (CVT model)
 Idemitsu CVTS-EX1
 Mazda JWS 3320
 MG Rover EM-CVT
 Mini Cooper EZL 799/EZL 799A/ZF CVT V1
 Mitsubishi CVT Fluid-MA1
 Mitsubishi CVTF-J1 (MMC Diaqueen CVT Fluid J1)
 Mitsubishi CVTF-J4 and -J4+ (MMC Diaqueen CVT Fluid J4 and J4+)
 Mitsubishi CVTF ECO J4
 Mitsubishi (Diaqueen) SP-III (CVT model only)
 Nissan NS-1, NS-2, NS-2V, NS-3, N-CVT
 Opel/Vauxhall 7-speed CVT, 95529854
 Perodua D-CVT

Peugeot PSA Standard 9735EF
 Punch CVTF-EX1 for Punch VT2/VT3/VT5 Transmissions
 Renault Elf Matic CVT
 Renault CVT CK/SK/FK
 Shell Green 1V Subaru iCVT, iCVT FG
 Subaru ECVT
 Subaru Lineartronic chain CVT & CVT II Fluid, K0425Y0710 & K0425Y0711
 Subaru Lineartronic chain CVT 3 Fluid
 Subaru Lineartronic High Torque (HT) CVT Fluid, CV-30, K0421Y0700
 Subaru High Torque CVTF-LV
 Suzuki CVTF TC
 Suzuki CVTF 3320, CVTF 4401
 Suzuki NS-2
 Suzuki CVT Green 1 & 2
 Suzuki CVT Green 1V
 Toyota CVTF TC
 Toyota CVTF FE
 Volvo CVT 4959
 VW/Audi TL 521 16 (G 052 516)
 VW/Audi TL 521 80 (G 052 180 A2)
 Zotye CVTs

eMobility Claims/Applications

Ford Escape Hybrid with eCVT
 Honda e:HEV
 Honda iMMD
 Jatco JR712E
 Jatco CVT 8 Hybrid
 Mazda SKYACTIVE-HYBRID
 Nissan e Power
 Nissan Altima Hybrid
 Toyota THSII/Toyota Prius
 Toyota THS 5th Gen. / Toyota Noah, Voxy etc.

This product should not be used for DCT applications





PRODUCT DATA SHEET

DuraMAX[®] CVT FLUIDS

SYNTHETIC CONTINUOUSLY VARIABLE TRANSMISSION FLUID



TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	AMBER	GREEN
Viscosity @ 40°C (cSt)	ASTM D445	34.0	34.0
Viscosity @ 100°C (cSt)	ASTM D445	7.3	7.3
Viscosity Index	ASTM D2270	188	188
Brookfield Viscosity @ -40°C, cP	ASTM D2983	9000	9000
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.852	0.852
Flash Point, °C/°F	ASTM D93	200/392	200/392
Pour Point, °C/°F	ASTM D5950	-45/-49	-45/-49
Color	ASTM D1500	Amber	Green

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used fluid and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur. Always follow manufacturers recommendations for fluid viscosity and service category. RelaDyne, LLC. assumes no responsibility for product misuse or improper application. For a copy of this product's Safety Data Sheet (SDS), visit www.RELADYNE.com (Rev 0126-01)

